

# Uf b-Quick-Ventà



Buitenkader - Dormant - Fixed frame

| W/m²K | P-19-A100 | P-19-A102 |
|-------|-----------|-----------|
|       | 0.96      | 0.85      |



T-profielen - Traverse - Transom

| W/m²K | P-19-A310 | P-19-A312 |
|-------|-----------|-----------|
|       | 0.95      | 0.86      |



Buitenkader/vleugel - Dormant/ouvrant - Fixed frame/vent

| W/m²K     | P-19-A240 | P-19-A242 |
|-----------|-----------|-----------|
| P-19-A100 | 1.06      | 0.94      |
| P-19-A102 | 0.98      | 0.89      |




Stolpraam - Mauclair - Double casement

| W/m²K | P-19-A240 + P-19-A440 | P-09-A242 + P-19-A442 |
|-------|-----------------------|-----------------------|
|       | 1.05                  | 0.88                  |



T-profiel/1 vleugel - Traverse/1 ouvrant - Transom/1 vent

| W/m²K     | P-19-A240 | P-19-A242 |
|-----------|-----------|-----------|
| P-19-A310 | 1.04      | 0.94      |
| P-19-A312 | 0.98      | 0.90      |



T-profiel/2 vleugels - Traverse/2 ouvrants - Transom/2 vents

| W/m²K     | P-19-A240 | P-19-A242 |
|-----------|-----------|-----------|
| P-19-A310 | 1.08      | 0.94      |
| P-19-A312 | 1.03      | 0.91      |